

Ref. 0202003

**Polyethylene Helmet with Ear Protection - CLIMAX**

**DESCRIPTION:**

- Helmet with earmuffs;

**0201004** Polyethylene helmet

**FEATURES:**

- Polyethylene injected harness with 6 fixation points (54-61 cm);
- Sweatband;
- Harness with manual adjustment through a ratchet system;
- Electrically insulating, designed for use in installations up to 1000 V in alternating current or 1500 V in direct current (CLASS 0);
- Lateral grooves allow for the attachment of a wide variety of accessories;
- Operating temperature: - 10°C / + 50°C;
- WEIGHT: 322g;

**0205008** ABS earmuff

**FEATURES:**

- Inner shell made of 20 mm foam with a 20 mm foam contour, covered with synthetic mousse;
- Mounting support for helmet adjustment made of polyamide and fiberglass with a metallic interior;
- Adjustable to fit various head shapes;
- SNR: 30dB;

**BRAND:** CLIMAX



**Standards:**



EN 352-3



EN 397-2012+A1-2012



EN 50365-2002

**Product Data:**

<b>Harness Material</b>	Polietileno
<b>Fixing Points</b>	6
<b>Sweat Band</b>	Sim
<b>Packaging</b>	20 Unidade(s) por Cartão
<b>Material</b>	Polietileno
<b>Model</b>	5P
<b>Type</b>	Capacetes
<b>Ventilated</b>	Não
<b>Setting</b>	Manual
<b>Color</b>	Amarelo, Azul, Branco, Castanho, Cinzento, Laranja, Verde, Vermelho
<b>Weight</b>	6
<b>Datasheet Version</b>	0202003.26032026/V4

Frequências (Hz)	125	250	500	1000	2000	4000	8000
Atenuação média (dB)	18,7	22,8	27,3	30,4	40,5	45,4	29,4
Desvio padrão (dB)	5,8	5,8	3,6	3,7	4,0	6,1	6,9
Atenuação assumida (dB)	12,9	17,0	23,7	26,7	36,5	39,3	22,5